

[c o r k s p o r t]



Installation Instructions for the CorkSport 90-97 Miata Cooling Panel

Contents

- CorkSport Cooling Panel
- 2 Page Installation Instructions

Tools Required

- Philips Screwdriver

NOTE: The CorkSport Miata cooling panel can be installed with or without painting. If you are painting the panel your self make sure you give it enough time for the paint to dry/cure before installation.

Step 1: Open your hood.

Step 2: Locate and remove the four (4) plastic screws (#1 in Illustration A) with the Philips screwdriver.

Step 3: Remove the stock plastic panel (#2 in Illustration A)

Step 4: Carefully install the new CorkSport cooling panel. The best method is to hold the hood latch handle up (#3 in Illustration B) and put it through the cooling panel. Make sure you hold the handle up until the latch handle is all the way through so not to scratch the top. Move the windshield washer fluid bottle lid (#4 in Illustration B) through before setting the cooling panel flush.

Thank you for your purchase. If you have any questions please call Cork Sport at 360 260 CORK

Step 5: Line up the two (2) small holes (#5 in Illustration B) and install the plastic screws from the stock panel through the holes.

Step 6: Take a soft cloth and wipe away the fingerprints and you are ready to go.

Illustration A



Illustration B



Thank you for your purchase. If you have any questions please call Cork Sport at 360 260 CORK